



TBU

SERIES

The best

of our
Compost-Windrow-Turners



WILLIBALD

- 1 Original Willibald high duty rubber discharge conveyor.
- 2 Milling drum with 28 knives.
- 3 Easy handling through 3-point lifter.
- 4 Hydraulically adjustable discharge flap for infinitely adjustable discharge height and range.



Our proven compost-turning-principle.



Transport position



Working position



Direct
drive via
PTO shaft

TBU SERIES

Mixing of the windrow ■

The removal of horizontal layers ensures that the outer and inner windrow layers are optimally mixed. The special arrangement of the blade type tools of the milling cylinder guarantees that these layers are milled off precisely so that the sidewalls of the windrow do not collapse.

Changing equipment ■

The mounting and removal of the TBU from the wheel loader is an easy matter by the use of quick release couplings.

Achtung Gefahr
Attention Danger

The hydraulically adjustable blades assures a correct and proper and to the windrow



Technical specifications



Technical specifications	TBU 3P
Operating mode	fixed at the 3-point linkage of a tractor of at least 130 hp engine power with creep-speed option that starts at 0,5 km/h
Drive	via tractor power take off (PTO)
Throughput	up to 1200 m ³ /h
Operation control unit	via tractor hydraulic system
Dimensions in mm l x w x h	4850 x 2450 x 3450
When folded for transport	3250 x 2450 x 4250
Mass	3200 kg
Width of conveyor belt	100 cm
Milling depth	up to 50 cm, depending on tractor type used and quality of material processed

For details
www.willibald-gmbh.de

March 2005
Technical changes reserved



WILLIBALD

J. Willibald GmbH Bahnhofstraße 6 · D-88639 Wald-Sentenhart
Tel. +49 (0) 75 78 / 18 90 · Fax +49 (0) 75 78 / 18 91 70
e-mail: info@willibald-gmbh.de www.willibald-gmbh.de