



**Officine meccaniche CERIM S.p.A.**

27029 Vigevano (Italy) - Corso Novara, 218 - P.O. Box 110

Tel. (+39) 0381 20905 - Fax (+39) 0381 24358

www.cerim.com - E-mail: info@cerim.com

## K175

### CARDATRICE AUTOMATICA DEL BORDO PER SUOLE A SCATOLA AUTOMATIC SIDE WALL ROUGHING MACHINE



CARATTERISTICHE TECNICHE	TECHNICAL FEATURES	
dimensioni	dimensions	mm 920x1950x2200
dimensioni imballo	packing dimensions	mm 1220x2250x2350
Peso netto	net weight	kg 960
peso lordo in cassa	gross weight in case	kg 1120
potenza elettrica totale installata	installed electrical power	kw 8,8
potenza elettrica motore	motor electrical power	kw 5,5
potenza elettrica assorbita media	average absorbed electrical power	kw 7
Produzione oraria fino a	Hour production up to	150 p/h



#### Caratteristiche :

- Sei assi programmabili
- Altissima definizione del profilo di cardatura/incollaggio
- Differenti pressioni e differenti velocità dell'utensile per ogni punto programmato
- Facilità di programmazione e correzione del profilo
- Alta produttività: fino a 150 paia/h
- Nuovo disegno e struttura ergonomicamente avanzata.
- Trasmissione dati per Isola di Montaggio o sistemi CAD/CAM.
- Autodiagnostica.



#### Features :

- Six programmable axis
- Extreme accuracy of margin roughing/cementing
- Pressure and speed of tools can be varied at any programmed point
- Simple programming and correction of margin
- High output: up to 150 pairs per hour
- The machine has been ergonomically designed to increase productivity.
- The machine is capable of data transmission within the Rink System or CAD/CAM system.
- The machine is self-diagnostic to assist fault finding.

I dati riportati su questo depliant potrebbero subire lievi modifiche senza preavviso

The company reserves the to supply products which may differ slightly from those described and illustrated in this publication